

# Hydraulic Power Unit / High Flow Power Unit



This 3-point auxiliary hydraulic unit allows you to operate attachments on tractors that don't generate enough hydraulic horsepower on their own like a snowblower or mower.



THE HYDRAULIC PUMP OFFERS SUPERIOR PERFORMANCE OVER ANY OF OUR COMPETITORS BECAUSE IT GENERATES HIGHER GALLONS PER MINUTE

MATCH OUR HYDRAULIC SNOWBLOWER AND POWER UNIT TO WORK UNIVERSALLY ON ANY TRACTOR AND LOADER THAT HAS THE SKID STEER LOADER ATTACHMENT CARRIER

THIS SELF-CONTAINED UNIT PRODUCES ENOUGH GALLONS PER MINUTE ALLOWING YOU TO OPERATE THESE HYDRAULICALLY-DRIVEN ATTACHMENTS





Take a Picture of This QR Code With Your Smart Phone to See it in Action



Cat II hitch & Cat III hitch quick hitch compatible



High Flow Power Unit shown here



Works with all tractors 30-150 PTO horsepower, tractor loader must have skid steer loader attachment carrier

*Optional:* high capacity oil cooler with thermostatically controlled 12-volt fan maintains proper oil temperature with low pressure loss. Internal bypass valve keeps the cooler from over-pressurizing

Cat I hitch & Cat II hitch quick hitch compatible



Hydraulic Power Unit shown here

## FEATURES & BENEFITS

- Provides hydraulic power to operate front loader attachments
- Built-in mounting brackets for optional oil cooler
- Convenient sight gauge allows for quick and easy checking of oil level
- Heavy-duty 10 gauge steel tank holds 33 gallons of oil
- 1,000 watt oil cooler and thermometer are standard on HP35 only
- 4,000 psi pressure relief valve protects system components from pressure spikes. HP35 only

## SPECIFICATIONS / OPTIONS

Model	HP15	HP20	HP24	HP35
Part Number	900900	900901	900902	920284
PTO Range	30-43 HP	44-53 HP	54-75 HP	80-150 HP
GPM/psi	15 @ 3,000	20 @ 3,000	24 @ 3,000	35 @ 4,000
PTO Input	540 RPM at pump	540 RPM at pump	540 RPM at pump	540 RPM at pump
Hitch Category	Cat. I & II	Cat. I & II	Cat. I & II	Cat. II & III
Planetary Gear Box	Industrial	Industrial	Industrial	Industrial
Gear Pump	High pressure	High pressure	High pressure	High pressure
Reservoir Capacity	25 gallons	25 gallons	25 gallons	33 gallons
Weight	350 lb.	350 lb.	350 lb.	700 lb.
In-line Return Filter	10 micron	10 micron	10 micron	10 micron
Tank Construction	11 gauge steel	11 gauge steel	11 gauge steel	10 gauge steel

### Options

High Performance Oil Cooler

15' Hose\*

18' Hose\*

\* For more specification details please see our website [www.erskineattachments.com](http://www.erskineattachments.com)