

Front Mount Snowblower



Erskine® snowblowers have been quality proven since 1948. Snow removal companies rely on our blowers to be trouble free and ready to go!



QUICKLY CHEWS THROUGH DEEP DRIFTS
AND CLEARS TO THE BARE GROUND,
WIDTHS VARY FROM 60" TO 108"

STANDARD FEATURES INCLUDE HYDRAULIC
LIFT AND CHUTE ROTATION, BOLT-ON CUTTING
EDGE, AND ADJUSTABLE SKID SHOES

TRUE QUICK ATTACH SYSTEMS THAT
ALLOW EASY ON/OFF ATTACHMENT
IN APPROXIMATELY 5 MINUTES



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



No freeze-up chute
design seals out snow
and freezing slush

Standard hydraulic
orbit motor
chute rotator

Large open-flight
auger with
shear bolt
protection (models
925FM, 965FM,
1085FM)

Efficient transfer case rotates
on it's side providing clearance
for ease of installation and
removal (models 725FM,
925FM, 965FM, 1085FM)

Adjustable frame system fits
most makes/models of tractors
(hoses not included)

Efficient
4-blade fan
with shear bolt
protection

Reversible
bolt-on high-carbon
steel cutting edge

Heavy-duty
enclosed
drive chain

FEATURES & BENEFITS

- Quick mount/dismount
- Hydraulic lift and chute rotation
- Adjustable skid shoes
- Shaft drive for maximum efficiency

SPECIFICATIONS / OPTIONS

Model	620FM	725FM	925FM	965FM	1085FM
Part Number	920117	920119	920122	902123	902124
Stage	2	2	2	2	2
Width of Cut	60"	78" (w/wings)	90"	96"	108"
Cutting Height	29"	36"	36"	36"	36"
Auger Diameter	16" Open Flight	16" Open Flight	18" Open Flight	16" Dual	16" Dual
Fan Diameter	20" 4-Blade	24" 4-Blade	26" 4-Blade	30" 4-Blade	30" 4-Blade
Discharge Chute	270° Hydraulic Rotator*	270° Hydraulic Rotator*	270° Hydraulic Rotator***	270° Hydraulic Rotator***	270° Hydraulic Rotator***
PTO Speed	540 RPM	540 RPM	540 RPM	540 RPM or 1,000 RPM	540 RPM or 1,000 RPM
Casting Distance	Up to 30'	Up to 35'	Up to 40'	Up to 50'	Up to 50'
PTO Range	20 - 35 HP	35 - 65 HP	50 - 100 HP	90 - 175 HP	90 - 175 HP
Driveline Series	12	35	35	55	55
Cutting Edge	5/8" x 6" Reversible	5/8" x 6" Reversible	5/8" x 6" Reversible	5/8" x 6" Reversible	5/8" x 6" Reversible
Skid Shoes	Adjustable / Replaceable	Adjustable / Replaceable	Adjustable / Replaceable	Adjustable / Replaceable	Adjustable / Replaceable
Weight	1,200 lb.	1,450 lb.	2,150 lb.	3,000 lb.	3,100 lb.
Options					
Hydraulic Deflector					
Electric Deflector					
Hardened Skid Shoes	Standard	Standard	Standard	Standard	Standard
Urethane Skid Shoes			N/A	N/A	N/A
Urethane Cutting Edge			N/A	N/A	N/A
Rubber Cutting Edge			N/A	N/A	N/A
Truck Loading Chute	N/A				
Electric Deflector for TLC	N/A				

*Includes deflector & 3-position linkage. Hydraulic and electric are optional. **Truck loading chute with deflector control is optional