

Heavy-Duty Forestry Mulcher





Forestry Attachments



applications









FEATURES & BENEFITS

- Motor options 33 41 GPM
- · High-strength timing belt to prevent slippage and wear
- · Variable displacement motor

- Built-in motor protection
- · Adjustable push bar
- · Reversible carbide teeth for double the tooth life

SPECIFICATIONS / OPTIONS

Model	HFM1000	HFM1100	HFM1200	HFM1300
Part Number w/Steel Teeth	901398	901396	901397	901399
Part Number w/Carbide Teeth	900924	900922	900923	900925
Path Width	71"	71"	71"	71″
Rotor Width	60"	60"	60"	60"
Maximum Flow	36 GPM	36 GPM	41 GPM	41 GPM
Minimum Flow	33 GPM	33 GPM	37 GPM	37 GPM
Pressure	3,000 - 3,600 psi	3,600 - 4,500 psi	3,000 - 3,600 psi	3,600 - 4,500 psi
Maximum Brush	10"	10"	10"	10"
Number of Teeth	30	30	30	30
System Protection	Built-in	Built-in	Built-in	Built-in
Shipping (L x W x H)	71" x 38" x 64"			
Weight	2,600 lb.	2,600 lb.	2,600 lb.	2,600 lb.
Loader Specific Forestry Kit	Required	Required	Required	Required
Case Drain	Required	Required	Required	Required

Options

Steel Replacement Teeth (set)

Carbide Replacement Teeth (set)

Factory Installed Case Drain Coupler Factory Installed Couplers

Factory Installed High Flow Couplers

^{*} For more specification details please see our website www.erskineattachments.com