

Heavy-Duty Power Angle Broom



Industrial broom design offers a heavy-duty frame, oversized bearing, and larger motor drive block. The strong and simple-to-use parking stands need no tools and have no pins that can get lost. The floating tilt follows the contours of uneven surfaces for better bristle contact and even bristle wear.

ROBUST STORAGE STANDS



CLEAN UP PARKING AREAS



OSCILLATING DESIGN ALLOWS BROOM TO FOLLOW UNEVEN TERRAIN



Take a Picture of This QR Code With Your Smart Phone to See it in Action



Hood made from 14 Gauge steel and formed for added strength



More robust and larger diameter filament than most of our competitors

Multiple heavy-duty wafer packages available

Flip up storage stand, no snap pins needed



Direct-drive design with replaceable drive components allowing forward and reverse operation



Optional: Wire Harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/CASE/Bobcat (14-pin).



Optional: Pistol Grip Control Harness is required if skid steer is NOT equipped with attachment control system. (Only needed when ordering hydraulic angling model).

SKID STEER

FEATURES & BENEFITS

- 8° floating tilt allows broom to follow ground contour. This helps prevent bristle coning when angled
- Oversized 4" bearing on arbor
- Stronger reinforced frame
- Agnels side to side 30 degrees
- Easy flip down stands require no tools and no pins
- Larger 3" hex drive helps with longevity

SPECIFICATIONS / OPTIONS

Model	720HD / 720HDX / 720HDXL	840HD / 840HDX / 840HDXL	960HD / 960HDX / 960HDXL
Width	72"	84"	96"
Width Fully Angled	62" @ 30°	72.5" @ 30°	83" @ 30°
Broom Angle	Manual 30° / Hyd 30° / Hyd 30°	Manual 30° / Hyd 30° / Hyd 30°	Manual 30° / Hyd 30° / Hyd 30°
Drive System	Hydraulic Motor Direct-Drive	Hydraulic Motor Direct-Drive	Hydraulic Motor Direct-Drive
Skid Steer Flow Range	13-24 GPM	13-24 GPM	13-24 GPM
Wafer Diameter	32"	32"	32"
Wafer Sections (number)	38	44	50
Wafer Options	Poly/Poly-Steel	Poly/Poly-Steel	Poly/Poly-Steel
Weight	1,040 - 1,095 lb.	1,120-1,170 lb.	1,205 - 1,255 lb.
Reversible Valve Block	Included w/XL model	Included w/XL model	Included w/XL model

Options

Pistol Grip Control Harness*

Loader Specific Wire Harness*

Factory Installed Couplers

*Applies to Hydraulic Angling Models Only

* For more specification details please see our website www.erskineattachments.com