


Hydraulic Breaker











Construction & Concrete Attachments





Take a Picture of This QR Code With Your Smart Phone to See it in Action



Model 210x Mounting plate included (not shown)



Model 310x Mounting plate included (not shown)



Model 360x Mounting plate included (not shown)



Model 410x Mounting plate included (not shown)



FEATURES & BENEFITS

- Power booster for high performance and low vibration
- · Central lubrication
- Field replaceable bushing for easier maintenance
- Innovative design with fewer components for higher reliability
- · Effective noise and vibration damping
- Highly efficient internal control valve

SPECIFICATIONS/OPTIONS

Model	210X	310X	360X	410X
Part Number	901546	901547	901548	901538
Carrier Weight Class	4,400-9,900 lb.	6,600-13,200 lb.	8,800-19,800 lb.	11,000-26,500 lb.
Weight	600 lb.	715 lb.	825 lb.	1,035 lb.
Operating Pressure	1,595-2,030 psi	1,595-2,030 psi	1,450-2,030 psi	1,740-2,175
Oil Flow Range	8-13 GPM	9-16 GPM	12-20 GPM	16-24 GPM
Impact Rate	670-1,500 BPM	520-1,300 BPM	530- 1,200 BPM	530- 1,000 BPM

Options			
Options Moil Tool Point (standard)			
Chisel Tool Point			
Blunt Tool Point			
Factory Installed Couplers			

 $^{{}^{\}star}$ For more specification details please see our website www.erskineattachments.com

