

Mini Rotary Tiller





Mini Equipment

ANNIVERSARY



Take a Picture of This QR Code With Your Smart Phone to See it in Action



Bi-Directional rotation increases efficiency by saving time and labor



Direct-Drive motor gives higher production with lower maintenance

FEATURES & BENEFITS

- Tills up to 4" deep
- Bidirectional rotation increases efficiency by saving time and labor
- Replaceable, double edge, hardened tines for prolonged life
- Direct-drive motor gives higher production with lower maintenance

SPECIFICATIONS/OPTIONS

_ Model	Rotary Tiller Mini
Part Number	900916
Overall Width	50.5"
Tilling Width	37"
Tilling Depth	0 - 4"
Overall Height	19.5"
Number of Tines	32
Tine Rotation	Bidirectional
Weight	320 lb.
Driveline	1 Motor
Hydro Flow Needed	7-16 GPM
Hydro Pressure Needed	2,500 psi
Drive	Direct

Mounting Kit Configurations

ASV/Terex (RC/PT30)

Bobcat (MT-52/55, 463/S70)

Toro / Vermeer / Boxer / Ditch Witch / Ramrod / Kanga / Cormidi

Universal Mounting Plate (up to 1,000 lb. ROC and within rated flow)

Options

Factory Installed Couplers



^{*} For more specification details please see our website www.erskineattachments.com