

Rotary Tiller



This is a perfect tool for preparing gardens, food plots or seedbeds. The bidirectional rotation saves time and labor as it allows you to quickly pulverize soil and cover your tracks. The dual direct-drive motors and replaceable, double-edge hardened tines keep you in the fields working, not in the repair shop.



BREAKS GROUND UP TO 6" DEEP.
CHOOSE FROM 66" OR 78" MODELS



BI-DIRECTIONAL OPERATION
LIMITS WASTED MOVEMENT



BRING IN YOUR TROPHY WITH
INCREDIBLE FOOD PLOTS





Take a Picture of This QR Code With
Your Smart Phone to See it in Action



Dual direct-drive motors give high production with lower maintenance

Replaceable, double-edge, hardened tines for prolonged life

Bi-Directional rotation allows for clearing of rocks and debris with a simple reverse of flow

SKID STEER

FEATURES & BENEFITS

- Bi-directional rotation increases efficiency by saving time and labor
- Tills up to 6" deep
- Dual direct-drive motors give higher production with lower maintenance
- Replaceable, double-edge, hardened tines for prolonged life
- Easy adjust depth shoes to control tilling depth
- Operates in standard flow or high flow

SPECIFICATIONS / OPTIONS

| Model | 66" | 78" |
|--------------------------------------|---------------|---------------|
| Part Number | 900913 | 900915 |
| Overall Width | 79" | 91" |
| Tilling Width | 65.5" | 77.5" |
| Tilling Depth | 0-6" | 0-6" |
| Overall Height | 18" | 18" |
| Number of Tines | 40 | 48 |
| Tine Rotation | Bidirectional | Bidirectional |
| Weight | 795 lb. | 888 lb. |
| Driveline | 2 motors | 2 motors |
| Hydro Flow Required | 16-28 GPM | 22-41 GPM |
| Hydro Pressure Required | 2,500 psi | 3,000 psi |
| Drive | Direct | Direct |
| Options | | |
| Factory Installed Couplers | | |
| Factory Installed High Flow Couplers | N/A | |

* For more specification details please see our website www.erskineattachments.com