

SB300 Snowblower with Hydraulic Power Unit



FEATURES & BENEFITS

- Direct-drive hydraulic auger
- Replaceable bolt-on high-carbon steel cutting edge
- Hydraulic relief — no shear pins
- Hydraulic control valve with electric solenoid controls all chute functions

SPECIFICATIONS / OPTIONS

Model	48"	54"	60"	72"	78"	84"
Part Number w/HP15	901711	901712	901713	901714	901715	N/A
Part Number w/HP20	N/A	N/A	901716	901717	901718	N/A
Part Number w/HP24	N/A	N/A	901719	901720	901721	901722
Stage	2	2	2	2	2	2
Width of Cut	48"	55"	61"	73"	79"	85"
Cutting Height	29"	29"	29"	29"	29"	29"
Cutting Edge (bolt-on)	5/8" x 6"	5/8" x 6"	5/8" x 6"	5/8" x 6"	5/8" x 6"	5/8" x 6"
Auger Diameter	16" open flight	16" open flight	16" open flight	16" open flight	16" open flight	16" open flight
Fan Diameter	20" 4-blade	20" 4-blade	20" 4-blade	20" 4-blade	20" 4-blade	20" 4-blade
Chute Rotation	Hydraulic 270°	Hydraulic 270°	Hydraulic 270°	Hydraulic 270°	Hydraulic 270°	Hydraulic 270°
Pressure Relief	Auger	Auger	Auger	Auger	Auger	Auger
Casting Distance	Up to 30'	Up to 30'	Up to 30'	Up to 30'	Up to 30'	Up to 30'
Weight	1,055 lb.	1,098 lb.	1,123 lb.	1,181 lb.	1,209 lb.	1,236 lb.
Hoses	Included	Included	Included	Included	Included	Included
Hyd. Flow @ 3,000 psi	15-24 GPM	15-24 GPM	15-24 GPM	15-24 GPM	15-24 GPM	15-24 GPM
Operating Pressure	2,500-3,500 psi	2,500-3,500 psi	2,500-3,500 psi	2,500-3,500 psi	2,500-3,500 psi	2,500-3,500 psi
Standard Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard

Options

High Perf. Oil Cooler / 16' Hose / 18' Hose / Hardened Skid Shoes / Urethane Skid Shoes / Urethane Cutting Edge / Rubber Cutting Edge

* For more specification details please see our website www.erskineattachments.com

* For more specification details please see our website www.erskineattachments.com