

# Tilt Attachment



The Tilt Attachment connects as an adapter between a skid steer loader's quick attach and its attachment. Controlled from the loader seat, the Tilt Attachment permits a skid steer to cut grades, ditches and swales, and keep attachments level on hilly ground. Unlike other tilt attachments, the design provides the lateral stability and tilting accuracy required for smooth machine control.

ROTATES 17 DEGREES



EASILY MOUNTS TO ANY STANDARD SKID STEER QUICK ATTACH




DUAL CYLINDERS TO CUT INTO DIRT WITH EVEN THE MOST POWERFUL MACHINES





Take a Picture of This QR Code With  
Your Smart Phone to See it in Action



SKID STEER

## FEATURES & BENEFITS

- Large 5" Center Bushing
- Rotates left or right up to 17° from the skid steer's horizontal centerline, with equal operation and speed when tilting in either direction
- Dual cylinder design provides both smooth operation and superior tilting force

## SPECIFICATIONS / OPTIONS

Model	Tilt Attachment
Part Number	900639
Weight	470 lb.
Width	57.2"
Height	20.9"
Depth	11.13"
Oscillation	+/- 17°
Cylinders	2
Cylinder Bore	2.5"
Cylinder Rod	1.25"
Cylinder Stroke	6"
<b>Options</b>	
Hydraulic Control Valve Kit (for secondary functions)	
Pistol Grip Control Harness*	
Loader Specific Wire Harness*	
Factory Installed Couplers	
*Required for optional hydraulic control valve kit	